



# Potentiostat / Galvanostat

## Model 2551

### Table of Contents

1	General Description.....	1
2	Metrological Properties.....	2
2.1	Counter Electrode.....	2
2.2	Working Electrode.....	2
2.3	Reference Electrode.....	2
2.4	Polarization Capability.....	2
2.5	IR Compensation.....	2
2.6	Response Time.....	2
2.7	Meters and Interfaces.....	2
2.8	Digital Interface.....	3
2.9	Cell Connections.....	3
2.10	Power Supply and Dimensions.....	3
3	Implemented Electrochemical Techniques.....	3
3.1	Detection.....	3
3.2	Voltammetric.....	3
3.3	Stripping.....	4
4	Spare Parts.....	4



## 1 General Description

**Model 2551** is the smallest potentiostat of AMEL's tabletop series. It has been conceived to be a perfect compromise between affordability and performances. The instrument is fully controlled by VApeak software for both electrochemical or electroanalytical techniques. AMEL's electrochemical equipment reliability stands on long time experience dating back to 1959.



## 2 Metrological Properties

### 2.1 Counter Electrode

Voltage Output	± 19V max
Current Output	± 1,2A max
Slew Rate	0,01mV/s to 10V/s
Protection	Thermal, overload and short-circuit

### 2.2 Working Electrode

Current Measure	From 10nA to 1A Full Scale in 9 ranges
Current Resolution	From 10pA at 10nA Full Scale to 100µA at 1A Full Scale
Measuring Accuracy	< 1% of Full Scale in 10nA to 1µA ranges < 0,25% of Full Scale in 10µA to 1A range

### 2.3 Reference Electrode

Input Impedance	> 1TΩ
Input Capacitance	< 20pF (1m cable)
Biassing Current	< 10pA at 25°C
Common Mode Rejection	> 60dB full frequency response
Voltage Range	± 10V max
Input BNC	Grounded outer contact

### 2.4 Polarization Capability

Voltage	± 10V max
Current	± 1A max
Voltage Resolution	0,1mV
Current Resolution	10pA
Accuracy	± 0,2% & 0,1% (conversion at Full Scale)

### 2.5 IR Compensation

Positive Feedback Range 2Ω to 100MΩ (depending on current range)

### 2.6 Response Time

Potentiostatic Rise Time	< 1µs resistive load (1000Ω)
Galvanostatic Rise Time	< 17µs resistive load (1000Ω)



## 2.7 Meters and Interfaces

A/D Converter	16 BIT
D/A Converter	16 BIT
Temperature Meter	0 to +100°C with PT1000 probe (0,1°C resolution and $\pm 0,2^\circ\text{C}$ accuracy)
Sampling Rate	200 $\mu\text{s}$

## 2.8 Digital Interface

Connection	USB with full instrument control (baud rate 57600 – N – 8 – 1)
Memory	EEPROM 64kB – SRAM 32kB
Port Output	8 external accessories
I/O port	8 optional

## 2.9 Cell Connections

Cables	2, 3, 4 cables. BNC connector for Reference (Hi & Low) and PL258 for Working and Counter electrodes.
--------	------------------------------------------------------------------------------------------------------

## 2.10 Power Supply and Dimensions

Voltage Mains	115 or 230V AC $\pm 10\%$ 50/60Hz
Power Consumption	60VA max
Dimensions (L x W x H)	400 x 440 x 85mm
Weight	8kg

## 3 Implemented Electrochemical Techniques

### 3.1 Detection

AD	Amperometric Detection
PD	Potentiometric Detection
DSA	Double Step Amperometry
DSV	Double Step Potentiometry
PAD	Pulsed Amperometric Detection

### 3.2 Voltammetric

LSV	Linear Scan Voltammetry
CYV	Cyclic Voltammetry
GLV	Galvanostatic Linear Voltammetry
GCV	Galvanostatic Cyclic Voltammetry
SWV	Square Wave Voltammetry
NPV	Normal Pulse Voltammetry
ACV	Alternating Current Voltammetry



PRODUCT CODE:

Model 2551

REVISION:

16/01/2020

PAGE:

4 of 4

- DPV Differential Pulse Voltammetry  
DNV Differential Normal Pulse Voltammetry  
DAV Differential Alternate Pulse Voltammetry

### 3.3 Stripping

- LSS Linear Scan Stripping  
ACS Alternate Current Stripping  
SWS Square Wave Stripping  
DAS Differential Stripping  
DPS Differential Pulse Stripping  
DNS Differential Normal Pulse Stripping  
PSA Potentiometric Stripping Analysis  
CCSA Constant Current Stripping Analysis

## 4 Spare Parts

- 191/GPC Grid power cable  
191/USB USB cable  
191/4BN4 Set of 4 WE, RE and CE cables  
191/C4 Set of 4 crocodile clips for WE, RE and CE 4mm banana plugs